600V N-Channel Super Junction power MOSFET

DESCRIPTION

SJ MOSFET is an advanced technology for high voltage power MOSFETs, designed according to the super junction principle by Xinyuan semiconductor. The offered devices provide all benefits of a fast switching and low on resistance, making it especially suitable for applications which require more efficient, more compact, lighter, High Performance Adapter etc.

V_{DS}	600	V
$R_{DS(ON)}$	70	mΩ
I_D	47	A

TO-220



TO-220F



TO-247



Features

- Extremely low losses due to very low R_{dson}*Q_g
- Superior Avalanche Rugged Technology
- Fast switching capability
- 100% Avalanche Tested
- Pb-free lead plating; ROHS compliant

APPLICATIONS

- Power factor correction（PFC）
- Switched mode power supplies(SMPS)
- Uninterruptible Power Supply（UPS）
- High Performance Adapter
- LED Lighting Power

ORDERING INFORMATION

Temperature Range	Package		Orderable Device	Package Qty.
-55°C ~ +125°C	TO-220	Pb-Free	CWH60R070AC	50 PCS/Tube
	TO-220F		CWH60R070AF	50 PCS/Tube
	TO-247		CWH60R070AZ	30 PCS/Tube

ABSOLUTE MAXIMUM RATINGS

（T_j=25°C, unless otherwise noted）

Parameter	Symbol	Value	Unit
Drain-Source Voltage (V_{GS}=0V)	V_{DSS}	600	V
Gate-Source Voltage (V_{DS}=0V, static)	V_{GS}	±30	V
Continuous Drain Current(T_C=25 °C)(Note1)	$I_{D(DC)}$	47	A
Continuous Drain Current(T_C=100 °C)(Note1)	$I_{D(DC)}$	30	A
Pulsed Drain Current(Note2)	I_{DM}	140	A
MOSFET dv/dt ruggedness, V_{DS}≤480 V	dv/dt	50	V/nS
Single Pulsed Avalanche Energy(Note3)	E_{AS}	1440	mJ
Avalanche Energy, Repetitive(Note1)	E_{AR}	2	mJ
Avalanche Current, Repetitive(Note1)	I_{As}	17	A
Maximum Power Dissipation（T_C=25 °C）	P_D	TO-220：219 TO-220F：34 TO-247：280	W
Operating, Storage Temperature Range	T_J, T_{STG}	-55~150	°C

THERMAL CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Units
Thermal Resistance, Junction-to-Case	R_{thJC}	-	-	TO-220：0.57 TO-220F：3.65 TO-247：0.45	°C /W
Thermal Resistance, Junction-to-Ambient	R_{thJA}	-	-	TO-220：62 TO-220F：80 TO-247：62	°C /W

ELECTRICAL CHARACTERISTICS

（T_j =25°C, unless otherwise noted）

Parameter	Symbol	Test Conditions	Min.	TYP.	Max.	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=1mA	600	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=600V, V_{GS}=0V	-	-	1	μA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±30V, V_{DS}=0V	-	-	±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS}=V_{DS}, I_D=1mA	2.0	3.0	4.0	V
Drain-Source On-state Resistance	$R_{DS(on)}$	V_{GS}=10V, I_D=23.5A	-	0.065	0.07	Ω
Gate Resistance	R_g	F=1MHZ, open drain	-	7.36	-	Ω

Dynamic Characteristics

（T_j = 25°C, unless otherwise noted）

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Input capacitance	C_{iss}	V_{DS}=100V, V_{GS}=0V, f=1MHz	-	3500	-	pF
Output capacitance	C_{oss}		-	138	-	
Reverse transfer capacitance	C_{rss}		-	5.0	-	
Turn-on delay Time	$t_{d(on)}$	V_{DD}=400V, I_D=23.5A R_G=3.3Ω, V_{GS}=10V	-	59	-	ns
Rise time	t_r		-	56		
Turn-off delay time	$t_{d(off)}$		-	360		
Fall time	t_f		-	57		

Gate charge characteristics

（T_j = 25°C, unless otherwise noted）

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Gate to Source Charge	Q_{gs}	V_{DD}=400V, I_D=23.5A V_{GS}=0 to 10V	-	20.9	-	nC
Gate to Drain Charge	Q_{gd}		-	16.3	-	
Gate Charge Total	Q_g		-	65.2	-	
Gate Plateau Voltage	$V_{plateau}$		-	5.6	-	V

Reverse diode characteristics

（T_j = 25°C, unless otherwise noted）

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Body Diode Forward Voltage	V_{SD}	V_{GS}=0V, I_{SD}=47A	-	0.9	-	V
Reverse Recovery Time	t_{rr}	V_R=400V, I_F=23.5A dI_F/dt=100A/μs	-	452	-	nS
Reverse Recovery Charge	Q_{rr}		-	8.23	-	μC
Peak Reverse Recovery Current	I_{rrm}		-	32.1	-	A

Notes:

1. Limited by maximum junction temperature;
2. Pulse width limited by maximum junction temperature;
3. I_{AS} = 17A, V_{DD} = 50 V, R_G = 25 Ω, Starting T_J = 25°C.

Electrical Characteristics Diagrams

Figure 1. Safe operating area	Figure2. Transient thermal impedance
	
$I_D=f(V_{DS})$; $T_c=25^oC$; parameter t_p	$Z_{(thJC)}=f(t_p)$; parameter: $D=t_p/T$

Figure3. Typ. output characteristics	Figure 4. Typ. transfer characteristics
	
$I_D=f(V_{DS})$; $T_j=25^oC$; parameter: V_{GS}	$I_D=f(V_{GS})$; $V_{DS}=20V$

Figure5.Drain-source on-state resistance	Figure6. Drain-source breakdown voltage
	
$R_{DS(ON)}$=f(T_j); I_D=20A; V_{GS}=10V	$V_{BR(DSS)}$=f(T_j); I_D=10mA

Figure7. Forward characteristics of reverse diode	Figure 8. Typ. gate charge
	
I_F=f(V_{SD}); parameter: T_j	V_{GS}=f(Q_{gate}), ID=47A pulsed

Figure9: Typ. capacitances	Figure10: Avalanche energy
	
C=f(V_{DS}); V_{GS}=0; f=1MHz	E_{AS}=f(T_j); I_D=16A; V_{DD}=50V

Test Circuits

Switch time test circuit





Reverse diode characteristics test circuit and waveform





Unclaimed inductive switching test circuit & waveform





PHYSICAL DIMENSIONS

TO-220



Symbol	Dimension（mm）			Symbol	Dimension（mm）		
	Min	Nom	Max		Min	Nom	Max
A	4.37	4.57	4.77	E	9.80	10.00	10.20
A1	1.25	1.30	1.45	E3	7.00	-	-
A2	2.20	2.40	2.60	e	2.54(BSC)		
b	0.70	0.80	0.95	e1	5.08(BSC)		
b2	1.17	1.27	1.47	H1	6.30	6.50	6.80
c	0.40	0.50	0.65	L	12.75	13.50	13.80
D	15.30	15.60	15.90	L1	-	3.10	3.40
D1	8.90	9.10	9.30	ΦP	3.40	3.60	3.80
D2	5.50	-	-	Q	2.60	2.80	3.00

TO-220F



Symbol	Dimension（mm）			Symbol	Dimension（mm）		
	Min	Nom	Max		Min	Nom	Max
E	9.96	10.16	10.36	e	2.54(BSC)		
A	4.50	4.70	4.90	L	12.68	12.98	13.28
A1	2.34	2.54	2.74	L1	2.93	3.03	3.13
A2	0.30	0.45	0.60	ΦP	3.03	3.18	3.38
A4	2.56	2.76	2.96	ΦP3	3.15	3.45	3.65
c	0.40	0.50	0.65	F3	3.15	3.30	3.45
c1	1.20	1.30	1.35	G3	1.25	1.35	1.55
D	15.57	15.87	16.17	b1	1.18	1.28	1.43
H1	6.70(REF)			b2	0.70	0.80	0.95

TO-247



Symbol	Dimension（mm）			Symbol	Dimension（mm）		
	Min	Nom	Max		Min	Nom	Max
A	4.80	5.00	5.20	E1	13.00	13.30	13.60
A1	2.21	2.41	2.59	E2	4.80	5.00	5.20
A2	1.85	2.00	2.15	E3	2.30	2.50	2.70
b	1.11	1.21	1.36	e	5.44(BSC)		
b2	1.91	2.01	2.21	L	19.82	19.92	20.22
b4	2.91	3.01	3.21	L1	-	-	4.30
c	0.51	0.61	0.75	ΦP	3.40	3.60	3.80
D	20.80	21.00	21.30	ΦP1	-	-	7.30
D1	16.25	16.55	16.85	S	6.15(BSC)		
E	15.50	15.80	16.10	-	-	-	-

< Copyright >

All the Patent, Copyright and IP contained in this document belong to Xinyuan semiconductor, shall not be reproduced , copied, or used in other ways without permission.